

# Handheld tyre gauge

**MAX**

Art. No. 114518

Type No. 36.015



Exemplary illustration

These pressure gauges are effectively protected against shock and impact by means of a free-standing plastic cap. They can be loaded against gauge pressure and up to the maximum scale value.  
With push-in plug for DN 7.2 coupling.

## Technical data

Version	with lever connector
Measuring range	0 to 25 bar
Measuring range	0 - 350 psi
Description	not conformity assessed
Hose connection	G 1/4, swivelling
Hose length	50 cm
Pressure gauge display	analogue

## Commercial data

Customs tariff number	90262080
Country of origin	DE
eCl@ss 5.1.4	27200610
eCl@ss 9.0	27200610
UNSPSC_Code_v190501	41103311
UNSPSC_CodeDesc_v190501	Manometers

## Material informations

REACH SVHC1 substance name	lead
CAS no. SVHC 1	7439-92-1
RoHS materials notice	RoHS compliant
REACH Info	contains SVHC substance

## Product informations

Single-lever operation: Inflation, deflation and checking with a single handle

To check: lever in home position

To deflate: lever actuated half-way

To inflate: lever fully actuated

Pressure gauge: Ø 80 mm, horizontal operating position, overpressure-proof up to 16 bar, PE protective cap

Operating temperature: -10 to 60 °C

Lever plug and double-sided service station plug: For all tire valves with valve thread VG 8 (cars, trucks, motorcycles), in offset design, especially for dual tires and motorcycles

Also suitable for tire gas (nitrogen)

## Spareparts

	Art. No.	Type No.
Hose, tyre valve connector, length 50 cm, G 1/4 swivelling	114534	36.250
Pressure gauge 0 - 25 bar/350 psi 80 mm Ø, for plugging	114542	36.43