

Standard manual tyre gauge

Standard type

PLUS ||

Art. No. 114543

Type No. 39.011



Exemplary illustration

Robust, standard handheld tyre gauge with rubber sheath and pressure gauge with dual scale in bar / psi. With push-in plug for 7.2 - 7.8 mm coupling.

Technical data

| | |
|------------------------|------------------------|
| Version | with clip-on connector |
| Measuring range | 0 to 12 bar |
| Measuring range | 0 - 170 psi |
| Description | uncalibrated |
| Hose connection | G 1/4, rigid |
| Hose length | 40 cm |
| Pressure gauge display | analogue |

Commercial data

| | |
|-------------------------|------------|
| Customs tariff number | 84242000 |
| Country of origin | IT |
| eCl@ss 5.1.4 | 27200610 |
| eCl@ss 9.0 | 27200610 |
| UNSPSC_Code_v190501 | 41103311 |
| UNSPSC_CodeDesc_v190501 | Manometers |

Material informations

| | |
|----------------------------|-------------------------|
| REACH SVHC1 substance name | lead |
| CAS no. SVHC 1 | 7439-92-1 |
| RoHS materials notice | RoHS compliant |
| REACH Info | contains SVHC substance |

Accessories

| | Art. No. | Type No. |
|---|----------|----------|
| Multi purpose nozzle set, inserting into the momentary plug | 156436 | 39.707 |

Spareparts

| | Art. No. | Type No. |
|---|----------|----------|
| Pressure gauge Ø 63 mm, uncalibrated, connection rear | 136796 | 39.702 |
| Clip-on connector | 145773 | 39.501-1 |
| Hose with quick connector, length 40 cm, G 1/4 rigid | 137578 | 39.901 |