

Blow gun

die-cast aluminium nickel-plated

EASY

Art. No. 117444

Type No. 22 K/T



Exemplary illustration

Standard type without nozzle!

In combination with the safety nozzles described below, this blow gun meets a wide range of safety requirements. For blowing out and cleaning machines, workpieces, bore holes, hollow parts, etc.

Technical data

Temperature range	-10 to 50 °C
Max. operating pressure	10 bar
Nozzle	M12x1.25
Nozzle type	without nozzle
Material	nickel-plated die-cast aluminium
Material push pin	steel 2Cr13
Type of connection	G 1/4 IT
Connecting thread	G 1/4

Commercial data

Customs tariff number	84242000
Country of origin	TW
eCl@ss 5.1.4	21060801
eCl@ss 9.0	21060801
UNSPSC_Code_v190501	27131502
UNSPSC_CodeDesc_v190501	Compressed air gun

Material informations

REACH SVHC1 substance name	no
CAS no. SVHC 1	no CAS No.
RoHS materials notice	RoHS compliant
REACH Info	no SVHC substance included

Accessories

	Art. No.	Type No.
Standard nozzle, Hole Ø 1.5 mm, Connection M12x1,25, for all air guns made of aluminium / nickel-plated die-cast aluminium	114344	105/5
Silencing nozzle, Connection M12x1,25, for all air guns made of aluminium / nickel-plated die-cast aluminium	114345	106/6
Nozzle with protective shield, Connection M12x1,25, for all air guns made of aluminium / nickel-plated die-cast aluminium	114346	107/6
Extension nozzle, Nozzle hole 3.0 mm, nickel-plated brass, 100 mm long curved, Connection M12x1,25	114347	22/100
Extension nozzle, Nozzle hole 3.0 mm, nickel-plated brass, 150 mm long curved, Connection M12x1,25	114348	22/150
Extension nozzle, Nozzle hole 3.0 mm, nickel-plated brass, 250 mm long curved, Connection M12x1,25	114349	22/250
Extension nozzle, Nozzle hole 3.0 mm, nickel-plated brass, 100 mm long straight, Connection M12x1,25	114350	23/100
Extension nozzle, Nozzle hole 3.0 mm, nickel-plated brass, 150 mm long straight, Connection M12x1,25	114351	23/150
Extension nozzle, Nozzle hole 3.0 mm, nickel-plated brass, 250 mm long straight, Connection M12x1,25	114352	23/250
Extension nozzle, Nozzle hole 2.5 mm, nickel-plated brass, 400 mm long straight, Connection M12x1,25	114353	23/400
Low noise fine spray nozzle, M12x1.25, Safety nozzle standard design, nickel-plated steel, Brass, Nozzles-exterior Ø 10 mm	114354	22.101
Low noise fine spray nozzle, M12x1.25, Safety nozzle standard design, nickel-plated steel, Brass, Nozzles-exterior Ø 10 mm	114355	22.102
Low noise round nozzle, M12x1.25, Safety nozzle standard design, aluminium, Length 55 mm, Nozzles-exterior Ø 11 mm	114356	22.201
Low noise round nozzle, M12x1.25, Safety nozzle standard design, Aluminium, Length 50.0 mm, Nozzles-exterior Ø 12,5 mm	206348	22.202-2
Low noise round nozzle, M12x1.25, Safety nozzle standard design, Aluminium, Length 41.0 mm, Nozzles-exterior Ø 13 mm	114358	22.203
Low noise round nozzle, M12x1.25, Safety nozzle standard design, POM plastic, Length 41.0 mm, Nozzles-exterior Ø 17 mm	114360	22.205
Low noise round nozzle, M12x1.25, Safety nozzle standard design, Aluminium, Length 35.0 mm, Nozzles-exterior Ø 11 mm	114361	22.206
Low noise round nozzle, M12x1.25, Safety nozzle standard design, Die-cast zinc, Length 47.0 mm, Nozzles-exterior Ø 19 mm	114362	22.207
Low noise round nozzle, M12x1.25, Safety nozzle standard design, ABS plastic, Length 55.0 mm, Nozzles-exterior Ø 19 mm	114363	22.208
Low noise flat nozzle, M12x1.25, Safety nozzle standard design, nickel-plated brass, Length 100.0 mm, Nozzle width 21.5 mm	114364	22.401

Accessories

	Art. No.	Type No.
Low noise flat nozzle, M12x1.25, Safety nozzle standard design, nickel-plated brass, Length 100.0 mm, Nozzle width 29 mm	114365	22.402
Low noise flat nozzle, M12x1.25, Safety nozzle standard design, nickel-plated brass, Length 100.0 mm, Nozzle width 21 mm	114366	22.403
Blow gun holder for aluminium and plastic blow guns, incl. 2 brackets for 90°- or 45°- fixation, incl. screws	142249	BPH-1
Thread adapter, Aluminium, ET M12x1.25, IT G 1/4, Length 26 mm	133178	22.14
Mini pressure regulator, G 1/4 ET / ET, Working pressure (pre-set) 2 bar, PN max. 12 bar	101506	638.42
Mini pressure regulator, G 1/4 ET / ET, Working pressure (pre-set) 4 bar, PN max. 12 bar	101507	638.44
Mini pressure regulator, G 1/4 ET / ET, Working pressure (pre-set) 6 bar, PN max. 12 bar	101508	638.46
Adjustable nozzle, M12x1,25, 10 bar, aluminium	146698	22.501
Low noise round nozzle, M12x1.25, safety nozzle standard design, die-cast zinc, aluminium, length 41.0 mm, nozzles-exterior Ø17 mm	129880	DLRZAM12X125
Venturi nozzle (full jet nozzle), alu, hole Ø 2.5 mm, connection M12x1.25, for air guns made of alu / nickel-plated die-cast alu	207588	107/7-V