

# Pre-filter

**PLUS**

Art. No. 146928

Type No. FSPV.G34



Exemplary illustration

For filtering out solid impurities larger than 1  $\mu\text{m}$  and for moisture separation.  
For connection upstream of a micro-filter or a combination micro-filter/activated carbon filter.

## Technical data

Input pressure	4 - 16 bar
Temperature range	1,5 to 80 °C
Housing	aluminium
filter bowl	aluminium
Filter rating	1 $\mu\text{m}$
Particle separation	1 $\mu\text{m}$
Efficiency	99.999 %
Filter element	cellulose
End caps	plastic
Support sleeves	stainless steel SS307
Drainage layer	needle felt
Indicating range of differential pressure gauge	0 - 1 bar
Flow rate measurement	at $P_1 = 7$ bar and pressure drop $\Delta_p = 0.1$ bar
Thread	G 3/4
Flow rate	3000 l/min
A	130.0 mm
C	43.0 mm
D	286.0 mm
Version	with differential pressure gauge
Condensate drain	automatic bleeder valve
Recommended change intervals	every 8000 operating hours, at the latest after 12 months (filter element), once a year (bleeder valve)

## Commercial data

Customs tariff number	84213925
Country of origin	MY
eCl@ss 5.1.4	27293003
eCl@ss 9.0	27293003
UNSPSC_Code_v190501	40161505
UNSPSC_CodeDesc_v190501	Air filters

## Accessories

	Art. No.	Type No.
Connection set for 2 filter, G 3/4 to G 1 1/2	147702	VBSFSP.2.G34-G112
Connection set for 3 filter, G 3/4 to G 1 1/2	147704	VBSFSP.3.G34-G112
Wall mounting set for 1 filter, G 3/4 to G 1 1/2	147706	WMSFSP.G34-G112

## Spareparts

	Art. No.	Type No.
Differential pressure gauge, pre-, micro-, active charcoal filter	146967	FSPDM.0-1B
Automatic bleeder valve, G 1/4 to G 1 1/2	147707	AAFSPVM.G14-G112
Filter element, G 3/4	147714	FEFSPV.G34