

Solid rubber workshop hose set

»BluBird« series

PLUS

Art. No. 149562

Type No. WSG.BB.15,5X9,5.S5.DKSK



Exemplary illustration

Highly flexible, silicone-free hose for compressed air applications in workshop environments (compressed air supply for pneumatic tools, equipment for assembly stations, etc.), assembled with push-button safety coupling NW 7.4.

Not suitable for direct mounting on pulsating tools.

We recommend the use of our vibration dampers in accordance with ISO 6150, § 7.1.

Technical data

Max. Operating pressure at 23 °C	12 bar
Tube I.D.	9.5 mm
Tube O.D.	15.5 mm

Commercial data

Customs tariff number	40093200
Country of origin	IN
eCl@ss 5.1.4	27294101
eCl@ss 9.0	27294190
UNSPSC_Code_v190501	40142002
UNSPSC_CodeDesc_v190501	Air hoses

Accessories

	Art. No.	Type No.
Plug-in connector, I.D. 7.2 - 7.8, hardened / galvanised steel, Sleeve I.D. 6, Operating pressure 0 - 35 bar, Temp. -20°C to 100°C	107541	243.06 ST
Plug-in connector, I.D. 7.2 - 7.8, hardened / galvanised steel, Sleeve I.D. 8, Operating pressure 0 - 35 bar, Temp. -20°C to 100°C	107542	243.06 ST-8

Accessories

	Art. No.	Type No.
Plug-in connector, I.D. 7.2 - 7.8, hardened / galvanised steel, Sleeve I.D. 9, Operating pressure 0 - 35 bar, Temp. -20°C to 100°C	107543	243.07 ST
Plug-in connector, I.D. 7.2 - 7.8, hardened / galvanised steel, Sleeve I.D. 10, Operating pressure 0-35 bar, Temp. -20°C to 100°C	107544	243.07 ST-10
Plug-in connector, I.D. 7.2 - 7.8, hardened / galvanised steel, Sleeve I.D. 13, Operating pressure 0-35 bar, Temp. -20°C to 100°C	107545	243.10 ST
Nipple for couplings I.D. 7.2 - 7.8, hardened / galv. steel, G 1/8 ET, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C	107546	243.49 ST
Nipple for couplings I.D. 7.2 - 7.8, hardened / galv. steel, G 3/8 ET, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C	107548	243.51 ST
Nipple for couplings I.D. 7.2 - 7.8, hardened / galv. steel, G 1/2 ET, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C	107549	243.52 ST
Nipple for couplings I.D. 7.2 - 7.8, hardened / galv. steel, G 1/8 IT, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C	107550	243.54 ST
Nipple for couplings I.D. 7.2 - 7.8, hardened / galv. steel, G 1/4 IT, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C	107551	243.55 ST
Nipple for couplings I.D. 7.2 - 7.8, hardened / galv. steel, G 3/8 IT, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C	107552	243.56 ST
Nipple for couplings I.D. 7.2 - 7.8, hardened / galv. steel, G 1/2 IT, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C	107553	243.57 ST
Vibration damper with 300 mm PVC workshop hose, plug I.D. 7.2 - I.D. 7.8, G 1/4 ET, pressed, max. 15 bar, Temp. -20 °C to 60 °C	142182	VD-300-7,2-1/4

Spareparts

	Art. No.	Type No.
Pushbutton safety coupling I.D. 7.4, rotating, Aluminium, G 3/8 ET, Operating pressure max. 12 bar, Temp. -20 °C to 70 °C	199983	DKSKAG38