

# Solid rubber workshop hose set

»BluBird« series

**PLUS**

Art. No. 149564

Type No. WSG.BB.15,5X9,5.S20.DKSK



Exemplary illustration

Highly flexible, silicone-free hose for compressed air applications in workshop environments (compressed air supply for pneumatic tools, equipment for assembly stations, etc.), assembled with push-button safety coupling NW 7.4.

Not suitable for direct mounting on pulsating tools.

We recommend the use of our vibration dampers in accordance with ISO 6150, § 7.1.

## Technical data

|                                  |         |
|----------------------------------|---------|
| Max. Operating pressure at 23 °C | 12 bar  |
| Tube I.D.                        | 9.5 mm  |
| Tube O.D.                        | 15.5 mm |

## Commercial data

|                         |           |
|-------------------------|-----------|
| Customs tariff number   | 40093200  |
| Country of origin       | IN        |
| eCl@ss 5.1.4            | 27294101  |
| eCl@ss 9.0              | 27294190  |
| UNSPSC_Code_v190501     | 40142002  |
| UNSPSC_CodeDesc_v190501 | Air hoses |

## Accessories

|                                                                                                                                    | Art. No. | Type No.    |
|------------------------------------------------------------------------------------------------------------------------------------|----------|-------------|
| Plug-in connector, I.D. 7.2 - 7.8, hardened / galvanised steel, Sleeve I.D. 6, Operating pressure 0 - 35 bar, Temp. -20°C to 100°C | 107541   | 243.06 ST   |
| Plug-in connector, I.D. 7.2 - 7.8, hardened / galvanised steel, Sleeve I.D. 8, Operating pressure 0 - 35 bar, Temp. -20°C to 100°C | 107542   | 243.06 ST-8 |

## Accessories

|                                                                                                                                    | Art. No. | Type No.       |
|------------------------------------------------------------------------------------------------------------------------------------|----------|----------------|
| Plug-in connector, I.D. 7.2 - 7.8, hardened / galvanised steel, Sleeve I.D. 9, Operating pressure 0 - 35 bar, Temp. -20°C to 100°C | 107543   | 243.07 ST      |
| Plug-in connector, I.D. 7.2 - 7.8, hardened / galvanised steel, Sleeve I.D. 10, Operating pressure 0-35 bar, Temp. -20°C to 100°C  | 107544   | 243.07 ST-10   |
| Plug-in connector, I.D. 7.2 - 7.8, hardened / galvanised steel, Sleeve I.D. 13, Operating pressure 0-35 bar, Temp. -20°C to 100°C  | 107545   | 243.10 ST      |
| Nipple for couplings I.D. 7.2 - 7.8, hardened / galv. steel, G 1/8 ET, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C       | 107546   | 243.49 ST      |
| Nipple for couplings I.D. 7.2 - 7.8, hardened / galv. steel, G 3/8 ET, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C       | 107548   | 243.51 ST      |
| Nipple for couplings I.D. 7.2 - 7.8, hardened / galv. steel, G 1/2 ET, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C       | 107549   | 243.52 ST      |
| Nipple for couplings I.D. 7.2 - 7.8, hardened / galv. steel, G 1/8 IT, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C       | 107550   | 243.54 ST      |
| Nipple for couplings I.D. 7.2 - 7.8, hardened / galv. steel, G 1/4 IT, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C       | 107551   | 243.55 ST      |
| Nipple for couplings I.D. 7.2 - 7.8, hardened / galv. steel, G 3/8 IT, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C       | 107552   | 243.56 ST      |
| Nipple for couplings I.D. 7.2 - 7.8, hardened / galv. steel, G 1/2 IT, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C       | 107553   | 243.57 ST      |
| Vibration damper with 300 mm PVC workshop hose, plug I.D. 7.2 - I.D. 7.8, G 1/4 ET, pressed, max. 15 bar, Temp. -20 °C to 60 °C    | 142182   | VD-300-7,2-1/4 |

## Spareparts

|                                                                                                                           | Art. No. | Type No. |
|---------------------------------------------------------------------------------------------------------------------------|----------|----------|
| Pushbutton safety coupling I.D. 7.4, rotating, Aluminium, G 3/8 ET, Operating pressure max. 12 bar, Temp. -20 °C to 70 °C | 199983   | DKSKAG38 |