

Solid rubber workshop hose set

»BluBird« series

PLUS

Art. No. 149594

Type No. WSG.BB.15,5X9,5.S10.K72



Exemplary illustration

Highly flexible, silicone-free hose for compressed air applications in workshop environments (compressed air supply for pneumatic tools, equipment for assembly stations, etc.), assembled with quick-release coupling NW 7.4.

Not suitable for direct mounting on pulsating tools.

We recommend the use of our vibration dampers in accordance with ISO 6150, § 7.1.

Technical data

Max. Operating pressure at 23 °C	20 bar
Tube I.D.	9.5 mm
Tube O.D.	15.5 mm

Commercial data

Customs tariff number	40093200
Country of origin	IN
eCl@ss 5.1.4	27294101
eCl@ss 9.0	27294190
UNSPSC_Code_v190501	40142002
UNSPSC_CodeDesc_v190501	Air hoses

Accessories

	Art. No.	Type No.
Plug-in connector for couplings I.D. 7.2 - 7.8, bright brass, Sleeve I.D. 6, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C	107232	243.06
Plug-in connector for couplings I.D. 7.2 - 7.8, bright brass, Sleeve I.D. 8, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C	107233	243.351

Accessories

	Art. No.	Type No.
Plug-in connector for couplings I.D. 7.2 - 7.8, bright brass, Sleeve I.D. 9, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C	107234	243.07
Plug-in connector for couplings I.D. 7.2 - 7.8, bright brass, Sleeve I.D. 10, Operating pressure 0 - 35 bar, Temp. -20°C to 100°C	107235	243.352
Plug-in connector for couplings I.D. 7.2 - 7.8, bright brass, Sleeve I.D. 13, Operating pressure 0 - 35 bar, Temp. -20°C to 100°C	107236	243.10
Nipple for couplings I.D. 7.2 - 7.8, bright brass, G 1/8 ET, Operating pressure 0-35 bar, Med./ ambient temp. -20°C to 100°C	107237	243.48
Nipple for couplings I.D. 7.2 - 7.8, bright brass, G 1/4 ET, Operating pressure 0-35 bar, Med./ ambient temp. -20°C to 100°C	107238	243.50
Nipple for couplings I.D. 7.2 - 7.8, bright brass, G 3/8 ET, Operating pressure 0-35 bar, Med./ ambient temp. -20°C to 100°C	107239	243.51
Nipple for couplings I.D. 7.2 - 7.8, bright brass, G 1/2 ET, Operating pressure 0-35 bar, Med./ ambient temp. -20°C to 100°C	107240	243.52
Nipple for couplings I.D. 7.2 - 7.8, bright brass, G 1/8 IT, Operating pressure 0-35 bar, Med./ ambient temp. -20°C to 100°C	107241	243.54
Nipple for couplings I.D. 7.2 - 7.8, bright brass, G 1/4 IT, Operating pressure 0-35 bar, Med./ ambient temp. -20°C to 100°C	107242	243.55
Nipple for couplings I.D. 7.2 - 7.8, bright brass, G 3/8 IT, Operating pressure 0-35 bar, Med./ ambient temp. -20°C to 100°C	107243	243.56
Nipple for couplings I.D. 7.2 - 7.8, bright brass, G 1/2 IT, Operating pressure 0-35 bar, Med./ ambient temp. -20°C to 100°C	107244	243.57
Nipple for couplings I.D. 7.2 - 7.8, bright brass, for hose 6x4, Operating pressure 0 - 35 bar, Med./ambient temp. -20°C to 100°C	107245	243.216
Nipple for couplings I.D. 7.2 - 7.8, bright brass, for hose 8x6, Operating pressure 0 - 35 bar, Med./ambient temp. -20°C to 100°C	107246	243.217
Nipple for couplings I.D. 7.2 - 7.8, bright brass, for hose 10x8, Operating pressure 0 - 35 bar, Med./ambient temp. -20°C to 100°C	107247	243.218
Nipple for couplings I.D. 7.2 - 7.8, bright brass, for hose 12x9, Operating pressure 0 - 35 bar, Med./ambient temp. -20°C to 100°C	107248	243.219
Nipple, I.D. 7.2-7.8, bright brass, for hose 6x4, Coupling nut, Kink protection, Operating pressure 0-35 bar, Temp. -20°C to 100°C	107249	243.355
Nipple, I.D. 7.2-7.8, bright brass, for hose 8x6, Coupling nut, Kink protection, Operating pressure 0-35 bar, Temp. -20°C to 100°C	107250	243.356
Nipple, I.D. 7.2-7.8, bright brass, for hose 10x8, Coupling nut, Kink protection, Operating pre. 0 - 35 bar, Temp. -20°C to 100°C	107251	243.357
Nipple, I.D. 7.2-7.8, bright brass, for hose 12x9, Coupling nut, Kink protection, Operating pre. 0 - 35 bar, Temp. -20°C to 100°C	107252	243.358
Plug-in angle for couplings I.D. 7.2 - 7.8, bright brass, for hose 6x4, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C	107253	243.760
Plug-in angle for couplings I.D. 7.2 - 7.8, nickel-plated brass, for hose 8x6, Operating pressure 0 - 35 bar, Temp. -20°C to 100°C	107254	243.761
Plug-in angle for couplings I.D. 7.2 - 7.8, bright brass, for hose 10x8, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C	107255	243.762
Nipple, I.D. 7.2 - 7.8, bright brass, G 1/4 ET, Thread coating, Operating pressure 0-12 bar, Medium / ambient temp. -20°C to 100°C	125654	243.50-EB
Nipple, I.D. 7.2 - 7.8, bright brass, G 3/8 ET, Thread coating, Operating pressure 0-12 bar, Medium / ambient temp. -20°C to 100°C	125655	243.51-EB

Accessories

	Art. No.	Type No.
Nipple, I.D. 7.2 - 7.8, bright brass, G 1/2 ET, Thread coating, Operating pressure 0-12 bar, Medium / ambient temp. -20°C to 100°C	125656	243.52-EB
Vibration damper with 300 mm PVC workshop hose, plug I.D. 7.2 - I.D. 7.8, G 1/4 ET, pressed, max. 15 bar, Temp. -20 °C to 60 °C	142182	VD-300-7,2-1/4

Spareparts

	Art. No.	Type No.
Quick-connect coupling I.D. 7.2, bright brass, G 3/8 ET, Operating pressure 0 - 35 bar, Med./ ambient temp. -20 °C to 100 °C	107209	243.02