

Spiral hose coupling set

Spiral hose, polyamide, PA12

MAX

Art. No. 158146

Type No. SP12250PADSK



Exemplary illustration

For safe and effective flow.

Thanks to their small coil diameter, they are compact, easy to handle and lightweight.

Not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Technical data


Operating temperature	-20 to 70 °C
Max. operating pressure at 23 °C	12 bar
Hose size	12x9 mm
No. of coils	9
Service length max.	2.5 m
Material	Polyamide, PA12
Shore hardness	65D
Coil O.D.	122 mm

with pushbutton-type safety coupling DN 7.4 and push-in plug, galvanised steel

Commercial data

Customs tariff number	39173300
Country of origin	CN
eCl@ss 5.1.4	27294101
eCl@ss 9.0	27294190
UNSPSC_Code_v190501	40142002
UNSPSC_CodeDesc_v190501	Air hoses

Service length



The service length is the maximum permissible extension (limit value).
After exceeding the limit value, a permanent deformation can occur.

Spareparts

	Art. No.	Type No.
Nipple for I.D. 7.2 - 7.8, hardened / galv. steel, G 3/8 IT	107552	243.56 ST
Spiral hose, Fitting, Polyamide, R 3/8, Hose Ø 12x9, 2.5 m	158122	SP12250PA
Pushbutton safety coupling I.D. 7.4, G 3/8 IT	199980	DKSKIG38