

**»multifix« series**

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design. The pressure setting can be locked by pushing the button down.

|                           |   |
|---------------------------|---|
| Max. input pressure:      | 16 bar  |
| Medium temperature:       | -10 to 60 °C  |
| Ambient temperature:      | -10 to 60 °C  |
| Spring bonnet:            | POM-brass   |
| Sealant:                  | NBR   |
| Flow rate measurement:    | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar |
| Internal air consumption: | Depending on secondary pressure   |

| Pressure regulator incl. pressure gauge |           |        |                    |                   |                 |      |    |
|---|-----------|--------|--------------------|-------------------|-----------------|------|----|
| Art. No.                                | Type No.  | Thread | Housing            | Control range bar | Flow rate l/min | Size | DN |
| 133100                                  | R 44 - 16 | G 3/4  | Die-cast aluminium | 0.5 - 16          | 12000           | 4    | 20 |

| Accessories / spare parts |           |  |
|---------------------------|-----------|--|
| Art. No.                  | Type No.  | Description  |
| 135858                    | ZW 45     | Mounting bracket with 2 screws                       |
| 135857                    | KP 45     | Coupler pack for modular assembly of several devices |
| 135855                    | 22.1845.4 | Set of wearing parts                                 |

