

»multifix« series

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.

The pressure setting can be locked by pushing the button down.

| | |
|---------------------------|---|
| Max. input pressure: | 16 bar |
| Medium temperature: | -10 to 60 °C |
| Ambient temperature: | -10 to 60 °C |
| Drain vale: | Semi-automatic |
| Spring bonnet: | POM-brass |
| Sealant: | NBR |
| Flow rate measurement: | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar |
| Internal air consumption: | Depending on secondary pressure |

Filter regulator with polycarbonate bowl, bowl guard and pressure gauge

| Art. No. | Type No. | Thread | Housing | Filter rating μm | Control range bar | Flow rate l/min | Size | DN |
|----------|-----------|--------|--------------------|-----------------------------|-------------------|-----------------|------|----|
| 133107 | C 44-S 10 | G 3/4 | Die-cast aluminium | 5 | 0.5 - 10 | 12000 | 4 | 20 |

Accessories / spare parts

| Art. No. | Type No. | Description |
|----------|-------------|--|
| 135858 | ZW 45 | Mounting bracket with 2 screws |
| 135857 | KP 45 | Coupler pack for modular assembly of several devices |
| 135859 | KSS 45 F-HA | Polycarbonate bowl, Bowl guard with semi-automatic draining |
| 135860 | KSS 45 F-A | Polycarbonate bowl, Bowl guard with fully automatic draining |
| 135861 | MS 45 FS | Metal bowl with sight glass and semi-automatic draining |
| 135862 | MS 45 FS-A | Metal bowl with sight glass and fully automatic draining |
| 100362 | 655.6.900 | Automatic drain valve |
| 135855 | 22.1845.4 | Set of wearing parts |
| 100144 | 6141.6.905 | Filter element 5 μm , cellpor |

