

The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses.

They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

Material:	Black steel
Max. working pressure:	50 bar
Surface:	Black steel
Standard thread:	acc. EN 10241



SFR23-1240-S

Double pipe nipples 23, male/male, black steel, DIN EN 10241

Art. No.	Type No.	Thread	Length mm
135359	SFR23-1440-S	R 1/4	40
135360	SFR23-1460-S	R 1/4	60
135361	SFR23-1480-S	R 1/4	80
135362	SFR23-14100-S	R 1/4	100
135363	SFR23-14120-S	R 1/4	120
135364	SFR23-14180-S	R 1/4	180
135365	SFR23-14200-S	R 1/4	200
135366	SFR23-3840-S	R 3/8	40
135367	SFR23-3860-S	R 3/8	60
135368	SFR23-3880-S	R 3/8	80
135369	SFR23-38100S	R 3/8	100
135370	SFR23-1240-S	R 1/2	40
135371	SFR23-1260-S	R 1/2	60
135372	SFR23-1280-S	R 1/2	80
135373	SFR23-12100-S	R 1/2	100
135374	SFR23-12120-S	R 1/2	120
135375	SFR23-12150-S	R 1/2	150
135376	SFR23-12200-S	R 1/2	200

Double pipe nipples 23, male/male, black steel, DIN EN 10241

Art. No.	Type No.	Thread	Length mm
135377	SFR23-3440-S	R 3/4	40.0
135378	SFR23-3460-S	R 3/4	60.0
135379	SFR23-3480-S	R 3/4	80.0
135380	SFR23-34100-S	R 3/4	100.0
135381	SFR23-34120-S	R 3/4	120.0
135382	SFR23-34180-S	R 3/4	180.0
135383	SFR23-34200-S	R 3/4	200.0
135384	SFR23-1040-S	R 1	40.0
135385	SFR23-1060-S	R 1	60.0
135386	SFR23-1080-S	R 1	80.0
135387	SFR23-10100-S	R 1	100.0
135388	SFR23-10120-S	R 1	120.0
135389	SFR23-10150-S	R 1	150.0
135390	SFR23-10180-S	R 1	180.0
135391	SFR23-10200-S	R 1	200.0
135392	SFR23-11440-S	R 1 1/4	40.0
135393	SFR23-11460-S	R 1 1/4	60.0
135394	SFR23-11480-S	R 1 1/4	80.0
135395	SFR23-114100S	R 1 1/4	100.0
135396	SFR23-114120S	R 1 1/4	120.0
135397	SFR23-114150S	R 1 1/4	150.0
135398	SFR23-114200S	R 1 1/4	200.0
135399	SFR23-11240-S	R 1 1/2	40.0
135400	SFR23-11280-S	R 1 1/2	80.0
135401	SFR23-112100S	R 1 1/2	100.0
135402	SFR23-112120S	R 1 1/2	120.0
135403	SFR23-112150S	R 1 1/2	150.0
135404	SFR23-112200S	R 1 1/2	200.0
135405	SFR23-2040-S	R 2	40.0
135406	SFR23-2060-S	R 2	60.0
135407	SFR23-2080-S	R 2	80.0
135408	SFR23-20100-S	R 2	100.0
135409	SFR23-20120-S	R 2	120.0
135410	SFR23-20150-S	R 2	150.0
135411	SFR23-20180-S	R 2	180.0
135412	SFR23-20200-S	R 2	200.0
135413	SFR23-21280-S	R 2 1/2	80.0
135414	SFR23-212100S	R 2 1/2	100.0
135415	SFR23-212120S	R 2 1/2	120.0
135416	SFR23-3080-S	R 3	80.0
135417	SFR23-30100-S	R 3	100.0
135418	SFR23-30120-S	R 3	120.0
135419	SFR23-30200-S	R 3	200.0