


With plastic cup, capacity approx. 1.0 litres, matte-transparent.

The spray fan of these guns can be adjusted with a nozzle according to requirements:  
Simply loosen the lock nut → adjust the nozzle → re-tighten the nut.

Operating pressure max.	10 bar
Recommended working pressure	about 2 - 6 bar
Operating temperature	5 °C to 50 °C
Nozzle	Ø 3 mm
Spraying cone	about 40°
Applications	Detergent, cold cleaners, spray oils

NOT suitable for acids, alkalis, flammable or toxic liquids.



11 B/E-1

13 B/E-1

Spray gun			
Art. No.	Type No.	Description	Type of connection
205458	11 B/E-1	Spray gun with straight spray pipe	Push-in plug for DN 7.2 coupling
205459	13 B/E-1	Spray gun with straight spray pipe and swivelling (360°) nozzle	Two-parts stem, I.D. 6

Spare parts for spray guns		
Art. No.	Type No.	Description
205460	14/H-1	Plastic cup, capacity 1.0 litres, incl. cover
114490	15/H	Metal cup, capacity 0.7 litres
114491	15/K	Metal lid
114492	16/H	Cork sealing ring (for metal cup)
117124	13.8.031	Air nozzle

14/H

**Air consumption / Capillary rise**

at different operating pressures and

Operating pressure [bar]		2	3	4	5	6	7	8
Air consumption [m³/h (l/min)]	stright pipe	2,5 (42)	3,0 (50)	3,6 (60)	4,3 (72)	5,0 (83)	5,7 (95)	6,5 (108)
	swivel pipe	3,2 (53)	4,2 (70)	5,2 (87)	6,3 (105)	7,4 (123)	8,5 (142)	9,6 (160)
Capillary rise [m]	stright pipe	4	5,5	6,5	7	6,5	5,5	4
	swivel pipe	2,5	4,2	5,5	6,0	6,5	7	6,5